BC 40/15

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/bc-40-15-p53897



Description

For reliable pumping of aggressive media

Areas of use

Pumping neutral and many non-neutral liquids, such as acids and bases, and aqueous solutions without abrasive components, e.g., in: - Surface technology - Environmental technology - Laboratory technology - Plastics industry - Rubber industry - Process engineering - Water treatment

Version

BC series plastic centrifugal pumps with mechanical seals are suitable for chemically neutral and many chemically non-neutral liquids. Many aqueous acids and bases can be pumped. The pumps are self-priming and feature a suction strainer. Reliable operation even with varying suction heads is ensured. Seals are available in Viton or EPDM. They are driven by standard three-phase or single-phase motors.

Technical data

Motor & drive

Motor frame size	80
Degree of protection	IP 55
Insulation class	F

Electrics

Frequency	50 Hz

Operating conditions & water

Ambient temperature (min.)	40 ° C

Hydraulic power

Head (min.)	19.3 mWS

Filtration

Lint catcher capacity	3 l
Strainer basket version	1
Strainer basket mesh size	ca. 3.2 mm x 2.6 mm

Connections & piping

Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Dimensions & logistics

Customs tariff number	84137051

Variants

Article number	Speed (max.)	Motor phases	Motor protection	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)	Rated current (230V)	Rated current (400V)	Energy efficiency class
2040154037	2,870 min-1	3~	ja	0.9 kW	0.75 kW	3~ 400/230 V	2.8 A	1.6 A	IE3
2040154038	2,885 min-1	1~	WSK 150°C	0.96 kW	0.75 kW	1~ 230 V	4.4 A	–	IE2
2040154337	2,905 min-1	3~	ja	1.2 kW	1 kW	3~ 400/230 V	4 A	2.3 A	IE3
2040154338	2,890 min-1	1~	WSK 150°C	1.25 kW	1 kW	1~ 230 V	5.5 A	–	IE2
2040154637	2,870 min-1	3~	ja	0.9 kW	0.75 kW	3~ 400/230 V	2.8 A	1.6 A	IE3
2040154638	2,885 min-1	1~	WSK 150°C	0.96 kW	0.75 kW	1~ 230 V	4.4 A	–	IE2
2040154837	2,905 min-1	3~	ja	1.2 kW	1 kW	3~ 400/230 V	4 A	2.3 A	IE3
2040154838	2,890 min-1	1~	WSK 150°C	1.25 kW	1 kW	1~ 230 V	5.5 A	–	IE2