BC 43/26

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/bc-43-26-p53913



Description

For reliable pumping of aggressive media

Areas of use

Pumping neutral and many non-neutral liquids, such as acids and bases, and aqueous solutions without abrasive components, e.g., in: - Surface technology - Environmental technology - Laboratory technology - Plastics industry - Rubber industry - Process engineering - Water treatment

Version

BC series plastic centrifugal pumps with mechanical seals are suitable for chemically neutral and many chemically non-neutral liquids. Many aqueous acids and bases can be pumped. The pumps are non-self-priming. Reliable operation even with varying suction heads is ensured. The seals are available in Viton or EPDM. They are driven by standard three-phase or single-phase motors.

Technical data

Hydraulic power

Head (min.)	22.7 mWS

Motor & drive

Motor frame size	90
Degree of protection	IP 55
Insulation class	F

Electrics

Frequency	50 Hz

Filtration

Lint catcher capacity	0 l

Connections & piping

Connection, inlet / suction side	Rp 2"
Connection, discharge side	Rp 2"
Recommended suction line diameter	75 mm
Recommended discharge line diameter	75 mm

Operating conditions & water

Ambient temperature (min.)	40 ° C

Dimensions & logistics

Customs tariff number	84137051

Variants

Article number	Name	Speed (max.)	Motor phases	Power input P_1 (max.)	Power output P_2 (max.)	Voltage (max.)	Rated current (230V)	Rated current (400V)	Energy efficiency class	Motor protection
2043263037	BC 43-26	2,900 min-1	3~	1.76 kW	1.5 kW	3~ 400/230 V	5.1 A	3 A	IE3	–
2043263438	BC 43/26	–	1~	2.66 kW	2.2 kW	1~ 230 V	12.8 A	–	IE2	Motorschutzschalter 14A