
SKG

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/skg-p53940



Technical data

Motor & drive

Speed (max.)	1,450 min-1
Degree of protection	IP 55

Electrics

Input voltage	400 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Operating conditions & water

Ambient temperature (min.)	40 ° C

Variants

Article number	Name	Flow rate	Head (min.)	Connection, inlet / suction side	Connection, discharge side
	SKG2001	–	–	–	–
	SKG2001 - 2008	3 m³/h	22 mWS	DN 20	DN 20
	SKG3201	–	–	–	–
	SKG3201 - 3208	5.3 m³/h	320 mWS	DN 32	DN 32
	SKG3301	–	–	–	–
	SKG3301 - 3308	7.5 m³/h	245 mWS	DN 32	DN 32
	SKG4001	–	–	–	–
	SKG4001 - 4008	12 m³/h	235 mWS	DN 40	DN 40
	SKG5001	–	–	–	–
	SKG5001 - 5008	20 m³/h	261 mWS	DN 50	DN 50
	SKG6501	–	–	–	–
	SKG6501 - 6508	35 m³/h	296 mWS	DN 65	DN 65