Normblock 32

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/normblock-32-p54022



Description

The block design enables high circulation rates with minimal space requirements. The motor is replaceable without having to completely disassemble the pump or remove the mechanical seal. The highly wear-resistant bellows mechanical seal is independent of the direction of rotation and maintenance-free. It is also medium-lubricated via an internal circulation line, enabling long service life. The pump shaft made of stainless steel 1.4571 is additionally protected by a shaft sleeve, also made of stainless steel 1.4571. This prevents wear on the pump shaft. Directly mounted, low-noise, surface-cooled, replaceable DIN IEC three-phase standard motor. According to energy efficiency class IE3. Includes PTC thermistor.

Areas of use

Swimming pool water circulation and filter flushing, as well as the operation of pool attractions in public pools. Also applicable for irrigation, drainage, water supply, shipbuilding, and industry.

Version

Normal suction single stage volute casing pumps with performance classification and main dimensions in accordance with NF E 11-112 and DIN EN 733 (replacement for DIN 24255). The pump and the replaceable standard motor are flanged together to form a block unit. The volute casings are fitted with replaceable corrosion resistant wear rings. The closed balanced impellers can be individually adapted to the respective operating conditions. Balancing is carried out to quality grade 6.3 in accordance with DIN ISO 1940. This ensures optimum smooth running and long service life of the entire pump. It is also available in three versions W05, W11 and W12. Each version features specially selected material combinations so that you can choose exactly the model that is best suited to your application and operating conditions.

Technical data

Electrics

Frequency	50 Hz

Variants

Article number	Name	Flow rate	Head (min.)	Power output P_2 (max.)	Voltage (max.)
6731114117	Normblock 32/125. 3~. 1.10 kW. W12. 1.450 min-1	34 m	27 mWS	1.1 kW	50 Hz 230 V Δ/400 V Y
6731034117	Normblock 32/125. Dr.. 0.37 kW. W12.	34 m	27 mWS	0.37 kW	50 Hz 230 V Δ/400 V Y
6731054117	Normblock 32/125. Dr.. 0.55 kW. W12.	34 m	27 mWS	0.55 kW	50 Hz 230 V Δ/400 V Y

Article number	Name	Flow rate	Head (min.)	Power output P_2 (max.)	Voltage (max.)
6731074117	Normblock 32/125. Dr.. 0.75 kW. W12.	34 m	27 mWS	0.75 kW	50 Hz 230 V Δ/400 V Y
6731152117	Normblock 32/125. Dr.. 1.50 kW. W12.	34 m	27 mWS	1.5 kW	50 Hz 230 V Δ/400 V Y
6731222117	Normblock 32/125. Dr.. 2.20 kW. W12.	34 m	27 mWS	2.2 kW	50 Hz 230 V Δ/400 V Y
6731302117	Normblock 32/125. Dr.. 3.00 kW. W12.	34 m	27 mWS	3 kW	50 Hz 400 V Δ/690 V Y
6731402117	Normblock 32/125. Dr.. 4.00 kW. W12.	34 m	27 mWS	4 kW	400 V
6731552117	Normblock 32/125. Dr.. 5.50 kW. W12.	34 m	27 mWS	5.5 kW	400 V
6732034117	Normblock 32/160. Dr.. 0.37 kW. W12.	37 m	39.5 mWS	0.37 kW	50 Hz 230 V Δ/400 V Y
6732054117	Normblock 32/160. Dr.. 0.55 kW. W12.	37 m	39.5 mWS	0.55 kW	50 Hz 230 V Δ/400 V Y
6732074117	Normblock 32/160. Dr.. 0.75 kW. W12.	37 m	39.5 mWS	0.75 kW	50 Hz 230 V Δ/400 V Y
6732114117	Normblock 32/160. Dr.. 1.10 kW. W12.	37 m	39.5 mWS	1.1 kW	50 Hz 230 V Δ/400 V Y
6732222117	Normblock 32/160. Dr.. 2.20 kW. W12.	37 m	39.5 mWS	2.2 kW	50 Hz 230 V Δ/400 V Y
6732302117	Normblock 32/160. Dr.. 3.00 kW. W12.	37 m	39.5 mWS	3 kW	50 Hz 400 V Δ/690 V Y
6732402117	Normblock 32/160. Dr.. 4.00 kW. W12.	37 m	39.5 mWS	4 kW	400 V
6732552117	Normblock 32/160. Dr.. 5.50 kW. W12.	37 m	39.5 mWS	5.5 kW	400 V
6732752117	Normblock 32/160. Dr.. 7.50 kW. W12.	37 m	39.5 mWS	7.5 kW	400 V
6733054117	Normblock 32/200. Dr.. 0.55 kW. W12.	36 m	60 mWS	0.55 kW	50 Hz 230 V Δ/400 V Y
6733074117	Normblock 32/200. Dr.. 0.75 kW. W12.	36 m	60 mWS	0.75 kW	50 Hz 230 V Δ/400 V Y
6733114117	Normblock 32/200. Dr.. 1.10 kW. W12.	36 m	60 mWS	1.1 kW	50 Hz 230 V Δ/400 V Y
6733154117	Normblock 32/200. Dr.. 1.50 kW. W12.	36 m	60 mWS	1.5 kW	50 Hz 230 V Δ/400 V Y
6733112117	Normblock 32/200. Dr.. 11.00 kW. W12.	36 m	60 mWS	11 kW	400 V
6733152117	Normblock 32/200. Dr.. 15.00 kW. W12.	36 m	60 mWS	15 kW	400 V
6733224117	Normblock 32/200. Dr.. 2.20 kW. W12.	36 m	60 mWS	2.2 kW	400 V
6733402117	Normblock 32/200. Dr.. 4.00 kW. W12.	36 m	60 mWS	4 kW	400 V
6733552117	Normblock 32/200. Dr.. 5.50 kW. W12.	36 m	60 mWS	5.5 kW	400 V
6733752117	Normblock 32/200. Dr.. 7.50 kW. W12.	36 m	60 mWS	7.5 kW	400 V
6734114117	Normblock 32/250. Dr.. 1.10 kW. W12.	39 m	95 mWS	1.1 kW	50 Hz 230 V Δ/400 V Y
6734154117	Normblock 32/250. Dr.. 1.50 kW. W12.	39 m	95 mWS	1.5 kW	50 Hz 230 V Δ/400 V Y
6734112117	Normblock 32/250. Dr.. 11.00 kW. W12.	39 m	95 mWS	11 kW	400 V
6734152117	Normblock 32/250. Dr.. 15.00 kW. W12.	39 m	95 mWS	15 kW	400 V
6734182117	Normblock 32/250. Dr.. 18.50 kW. W12.	39 m	95 mWS	18.5 kW	400 V
6734224117	Normblock 32/250. Dr.. 2.20 kW. W12.	39 m	95 mWS	2.2 kW	50 Hz 230 V Δ/400 V Y
6734222117	Normblock 32/250. Dr.. 22.00 kW. W12.	39 m	95 mWS	22 kW	400 V
6734304117	Normblock 32/250. Dr.. 3.00 kW. W12.	39 m	95 mWS	3 kW	50 Hz 400 V Δ/690 V Y
6734302117	Normblock 32/250. Dr.. 30.00 kW. W12.	39 m	95 mWS	30 kW	400 V
6734404117	Normblock 32/250. Dr.. 4.00 kW. W12.	39 m	95 mWS	4 kW	400 V
6734554117	Normblock 32/250. Dr.. 5.50 kW. W12.	39 m	95 mWS	5.5 kW	400 V
6734752117	Normblock 32/250. Dr.. 7.50 kW. W12.	39 m	95 mWS	7.5 kW	400 V