Normblock Binero 80

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/normblock-binero-80-p54057



Description

Characteristic curves, as well as dimensional drawings and the various material combinations can be found in detail in our design program at speck-select.com

Areas of use

Swimming pool water circulation for filtration and filter flushing, as well as the operation of swimming pool attractions in public swimming pools. > Outdoor and indoor pools > Thermal, medicinal, and spa baths > Pools with elevated brine concentrations > Water treatment, e.g., filter system construction > Leisure facilities > Attractions, e.g., water slides > Shipbuilding > Industry, e.g., cooling water systems > Water supply, e.g., irrigation

Technical data

Hydraulic power

Operating pressure max.	10 bar

Motor & drive

Speed (max.)	50 min-1
Degree of protection	IP 55
Insulation class	F

Electrics

Frequency	50 Hz

Operating conditions & water

Ambient temperature (min.)	40 ° C

Variants

Article number	Name	Head (min.)
	Normblock Binero 65-200	37 mWS
	Normblock Binero 65-250	37 mWS
	Normblock Binero 80-160	56 mWS
	Normblock Binero 80-200	56 mWS

Article number	Name	Head (min.)
	Normblock Binero 80-250	56 mWS