SFE 3-25

Product page https://www.speck-neos.medienreaktor-kunden.de/en/p/sfe-3-25-p54116



Description

Die vollautomatischen Mehrpumpdruckerhöhungs-Anlagen sind je nach Bedarfsfall mit 2 bis 6 Pumpen ausgestattet. Sie sind kompakt, geräuscharm und werden anschlussfertig verdrahtet und komplett verrohrt ausgeliefert. Alle Aggregate besitzen eine vollautomatische Pumpensteuerung. Die Druckerhöhungs-Anlage ist mit einer Frequenzregelung ausgestattet.

Technical data

Hydraulic power

Number of pumps	3 St

Motor & drive

Speed (max.)	2,850 min-1
Degree of protection	IP 55
Insulation class	F

Electrics

Input voltage	400 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Operating conditions & water

Ambient temperature (min.)	40 ° C

Variants

Article number	Name	Head (min.)	Operating pressure max.	Power output P_2 (max.)
5632502500	SFE 3/25-20	32.631 – 43.848 mWS	10 bar	4 kW
5632503500	SFE 3/25-30	50.986 – 65.262 mWS	10 bar	5.5 kW

Article number	Name	Head (min.)	Operating pressure max.	Power output P_2 (max.)
5632504500	SFE 3/25-40	69.341 – 86.676 mWS	10 bar	7.5 kW
5632505500	SFE 3/25-50	85.656 – 109.11 mWS	16 bar	11 kW